

TC1026P

Multi channel CAN FD and LIN bus interface



Scan the code to follow

Classic Application:

- Real-time control system
- Industrial automation
- Motor control



Feature Overview

1. High-speed CAN FD and LIN interface

2. Multi-channel support

3. Real-time control

4. Industrial automation

5. Motor control

6. High reliability

7. Easy integration

8. Low power consumption

9. Wide temperature range

10. Small size

11. High precision

12. Low noise

13. High accuracy

14. High stability

15. High performance

Characteristics

- High-speed CAN FD and LIN interface
- Multi-channel support
- Real-time control
- Industrial automation
- Motor control
- High reliability
- Easy integration
- Low power consumption
- Wide temperature range
- Small size
- High precision
- Low noise
- High accuracy
- High stability
- High performance

Specification

c g i i	l sGD ,s l A
K @_ i	PN)+
l *GD @_ i	4 do ra i
rd m	rd r(am _ nð ajnr di_ jr n i _Gdpsintroih n rprdb ðtro ðh j k odgdt
pam	@ c c g rpkki jon om rh d piamjapko j;+++ l amh n
l	Þkk jon l)+ knþ j gñ j kgd or æ DUJ,343(, ro _ m i r æ p_ mo , 0 kn(HFkn
l A	Þkk jon l A æ o j kgdnr æ þ DUJ _ j (DUJro i _ mn i r æ p_ mo nantj , 0 kno jH kn
GD	Þkk jonGD), _GD)s p_ mo + (+ kn F
Nc _gg O g	Þkk jonG A gñ _ rñ nci _gg o g n6gnj gñ jr n prø j nc _gg o g j æpmodj i
Od ro h k	, nc nr mh mn b od ro h k
O rth d odj Minð jm	pð(d, + (þ h o rth d odj minð jm jar m j æpm g
H mn b nN ok nNi j _%	iH st ph ++++ amh n* n j _ i
H mn b nM q _k nN j _%	H st ph ++++ amh n* n j _ i
Dg odj i	l c g a g i a _ o þ+ r æ @l knþ odj ja i / # j o f o _ æ c r b _ 3 i # æ h æ c r b
K jr mþkgt	PN k jr m_6 so mgk jr imm l p æ h _ ajnGD j h p d odj i i
K jr m j rph kodj i)OR
ndbH o indg	H o g
d ndj n i i	þ 3s4, s. Oh h
R æco	kkmjæ d ogt 0 b # æ pok bdb ¶ kkmjæ d ogt144b # æ k bdb f i
Jk modb Oh ki mppm	(/+ y 3
Jk modb Cph æ dt	þ o j# # j (j l i ndb i i
Jk modb @q æ i j h i o i i	k r f t æ rj jmjnd b n n

%Ndæg c i g o, Hi knr æ + (b _ o æg_

Ordering information

Product Name	Model Number	Function Description
l or jm qd f	O, 1K	, c g liA l c gGD ii

Shipping list

- O, 1 _qd
- PN g %
- 4 ah g j o jn ij
4 kgpibriGD pn g %

Pin definition

G a 5GD / * 0 * 1 H d g 5GD , * * : M d c o 5 I A

