



TC4016

多总线技术设备



CAN/CAN FD
 EENF PEI5
 DIDO AIAO

FC4016 EENF E[Y^WEVYWN[TT^MFdS`e_ [ee[a`
 PEI5 P^W^ZWS^EW^eadi` f^WSUW5 ECG E^W^U^da` [UCa
 `fda^G` [f EENF PEI5
 CAN/CAN FD /
 DIDO / AIAO

FC4016 PC
 EENF PEI5 CAN/CAN FD

I [Vai e L[gj API
 C++ C# LSTH[W PkfZa`

- ge
- I [Vai e
- 20 EENF 10 EPC
- 16 PEI5
- 2 CAN/CAN FD
- DIDO*4 AIAO*3
- CAN 125Ktbe-1MTbe
- CAN FD 8MTbe
- CAN 120
- CAN E^W^X^ACK
-
- API

	2 * CAN/CAN FD 4 * DIDO 3 * AIAO 20 * EENF(10 EPC) 16 * PEI5
PC	I [Vai e FEMSeFWd 120 1ge 20000 / 20000 /
	CAN DC2500H f 8KH f 15KH
DIDO	DI Op39.5H HdVX HdVX): Op3.28H DI :HAH=(330+499*HdVX)/1098; HS^=0.455*HdVX DO OH 5H/12H
AIAO	AI Op39.5H AO Op29.5H
EENF	3p50ge Op8N[TT W &
PEI5	/ 5.15H/6.65H/7.70H 13_ A/26_ A 125] Tbe/189] Tbe 33T[f Op480ge /CRC
	9p32HDC
	5l
	110*70*36_ _
	150Y / 368Y
	-40 80
	10% 90%

	FC4016	

FC4016

12H2A

DB9

DB9